

System Requirements

CRIBWARE SE (Multi-User, Non-Server Configuration)

The CRIBWARE[®] Standard Edition (SE) configuration is recommended for standalone or local area network installations with less than four CRIBWARE workstations. Multiple facility implementations are not recommended in this configuration.

CRIBWARE Workstation

- Pentium level III microprocessor, running at 600MHz or better
- Windows 2000 and XP Professional operating system, with the latest service packs installed
- 256 MB RAM or greater
- 200 MB of available disk space, with additional space recommended for data growth
- CD drive (16X speed or better)
- SVGA monitor (800 X 600 minimum resolution)
- Printer for report output
- Internet access for remote technical support
- Parallel or USB port for bar code printer or scanner (optional)
- Available PCI slot for CRIB-ACCESS electromagnetic lock mechanism (optional)
- Available serial port (RS-232) for the following devices (optional):
 - Stock Supervisor e-Lock interface
 - CRIBPOINT Vending machine
 - Crib Access (one port per input device)
 - CRIBMATE communications dock
 - Remstar Shuttle or Vertical Carousel interface
 - Kardex Industrier interface

Network (Optional)

- Using CRIBWARE software on a network requires 200MB or greater of network disk space and the file server should not be a primary domain server.
- Each workstation requires a suitable network card (10 Mbps minimum, 100 Mbps recommended) and network software consistent with the type of network installed

Bar Code Hardware (Optional)

- Wedge scanners – QuickScan[®] 6000 Plus, Powerscan[®] 7000BT, and PowerScan[®] M8300
- Batch Scanners – Intermec[®] CK-30
- Bar code printer – Zebra[™] TLP2844

Lista Cabinets (Optional)

- Making Workspace Work[™] style cabinets
- e-Lock bar locking mechanism and e-Lock interface with power supply
- Available serial port (RS-232) for e-Lock interface
- 110V Electrical power outlet

CRIBWARE Courier (Optional)

- Microsoft Outlook or Outlook Express e-mail client

System Requirements

CRIBWARE Server (LAN Configuration)

This configuration is recommended for local area network installations with four or more CRIBWARE clients or where network traffic is high enough to degrade performance. The server's role in the network infrastructure may require performance greater than outlined below. Each client should have network access to the CRIBWARE Server at a minimum of 10 Mbps. A TDS machine is not currently available in a Server configuration.

Server computer

- Pentium level III microprocessor running at 1.2GHz or better with a minimum 1 GB RAM
- Windows 2000 or 2003 Server operating system with latest service packs installed
- 200 MB of available disk space for program files and client installation files. The CRIBWARE database files require a minimum of 500MB of disk space, with additional space recommended for data growth.
- CD drive (16X speed or better)
- SVGA monitor (800 X 600 minimum resolution)
- Network card suitable for the type of network installed

Client Computer

- Each CRIBWARE client requires the same hardware, operating system and peripherals as specified for the CRIBWARE workstation.
- A TDS machine is not currently available as a client.

CRIBWARE Server (WAN Configuration)

This configuration is recommended for wide area network installations and/or multi-facility implementations. This solution is recommended when CRIBWARE clients access the network at less than 10 Mbps or where network traffic significantly degrades performance. The server's role in the network infrastructure may require performance greater than outlined below. A TDS machine is not currently available in a Server configuration.

Server computer

- Pentium level IV microprocessor running at 1.2GHz or better
- Windows Server operating system with the latest service packs installed
- Windows Terminal Server and/or Citrix Server (Two separate servers increase performance)
- 1 GB RAM or greater, depending upon the number of concurrent users per Terminal Server/citrix Server
- 200 MB of available disk space for program files and client installation files. The CRIBWARE database files require a minimum of 500MB of disk space, with additional space recommended for data growth.
- CD-ROM drive (16X speed or better)
- SVGA monitor (800 X 600 minimum resolution).
- Network Interface card suitable for the type of network installed.

Client Computer

- Each CRIBWARE client requires the same hardware, operating system and peripherals as specified for the CRIBWARE workstation.
- A TDS machine is not currently available as a client.

©2008 Applied CIM Technologies, Inc. All rights reserved. The information in this document is subject to change without notice. CRIBWARE is a registered trademark of Applied CIM Technologies, Inc. Windows is a registered trademark of Microsoft Corporation.